Sure - Clamp Access
Specifications

A. General Description: . **Rectangular** Clamping type removable ductwork section with draw latch.

B. Allowable leakage: 1/2 CFM for 2" W.G.

C. Provide size as indicated on drawings.

D. Size : 18" X 18" maximum size

E. Material : Galvanized ASTM A527

F. Flange Connection : 18 GA galvanized sheet metal construction.

G. Seams : Pittsburgh Lock

H. Access Section : Minimum 26 Gauge galvanized ASTM A527 18" long.
: Fabricated to maintain 100% of ductwork free area.

I. Clamps : 20 gauge galvanized with zinc coated draw latch. Gasket profile forms to the inside of clamp and seals the outer edges of the ductwork flange.

J. Gasket : Neoprene gasket 3/16" X 1-1/4"

K. Seal seams in accordance with SMACNA HVAC Duct Construction Standard - Metal and Flexible.

L. Install : The removable access section shall not be more than 4" away from the fire damper sleeve break away connection.

M. Manufacturer :

Langdon Inc.
9865 Wayne Ave Cincinnati, Ohio 45215
Phone (513)733-5955 ext.246 Fax (513)733-8050
www.langdonsheetmetal.com
Attn. : Jon Sandman - Mobile # 513-264-5599

Sure-Clamp Access